



StoCoat® Climasan® VLC* Odor Neutralizing Coating

StoCoat® Climasan® is an innovative interior flat wall and ceiling coating that when exposed to a light source will neutralize odors from the air. This easy to apply, single component acrylic latex requires no special equipment or application methods. Climasan contains Visible Light Catalytics (VLC) that continuously degrade organic compounds and pollutants and remains active for as long as the coating is exposed to light.

*Visible Light Catalytics



StoCoat® Climasan® Benefits:

Actively improves indoor air quality

- With VLC are activated by natural daylight or artificial interior lighting
- Degrades organic compounds to eliminate indoor odor
- VOC less than 5 grams per liter

Saves time and money

- High quality washable interior flat
- Dirt and surface stains clean off
- Use on both walls and ceilings
- Use on plaster, drywall, brick and CMU

Easy application and clean up

- Smooth flowing acrylic latex for exceptional hiding and finish
- Soap and water clean up



StoCoat® Climasan®	
Attributes	Interior Odor Neutralizing Coating Acrylic Latex Flat finish > 2% at 60° Hard wearing washable finish Easy to apply (Brush, Roller, Spray)
Recommended use	Walls and Ceilings Not recommended for kitchen and bathrooms or industrial applications
VOC Level (g/L)	< 5
% Solids by Volume	56%
Coverage (sqft/gal)	285-325
Dry-time: To touch/To recoat	2 hours / 6 hours
Colors	Selection of off white inorganic colors

Sto Corp.
3800 Camp Creek Parkway
Building 1400, Suite 120,
Atlanta, GA. 30331

Tel: 404-346-3666
Toll Free: 1-800-221-2397
Fax: 404-346-3119

www.stocorp.com



SB70A 03/15

This table highlights some of the key features of StoCoat® Climasan®. Please refer to the relevant technical data, SDS, label instructions and Hotlines Technical Notes for full specifications, application and performance data.

ATTENTION

This product must be applied in accordance with all Sto specifications instructions. To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. Sto Corp. disclaims all and assumes no liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

Contact your
Sto Sales Representative
for more information.
Please visit us at
www.stocorp.com
or call us toll-free at
800-221-2397.