

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product Name: StoColor Lotusan

Product Code: 80217 SDS Manufacturer Number: 80217

Product Use/Restriction: Waterbased Acrylic Coating.

Manufacturer Name: Sto Corp.

Address: 6175 Riverside Drive, SW

Atlanta, Georgia 30331

General Phone Number: (404) 346-3666 Emergency Phone Number: (800) 424-9300 SDS Creation Date: July 08, 2013

SDS Revision Date: March 1, 2017 (M)SDS

Format:





* Chronic Health Effects

1 of 8

SECTION 2 - HAZARD(S) IDENTIFICATION

GHS Pictograms:

Precautionary Statements:



GHS Class: Eye Irritant, Category 2

Skin Irritant, Category 2

Hazard Statements: Causes eye irritation Causes skin irritation

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Wash hands thoroughly after handling.

Emergency Overview: WARNING! Irritant.

Eyes. Skin. Inhalation. Ingestion. Route of Exposure:

StoColor Lotusan Product Code: 80217 Revision Date: 3/1/2017

Potential Health Effects:

May cause irritation. Eye: Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Amorphous silica	60676-86-0	5 - 10 by weight	
Cristobalite silica	14464-46-1	5 - 10 by weight	
Crystaline silica (Quartz)	14808-60-7	5 - 10 by weight	
Octyl triethoxy silane	35435-21-3	1 - 5 by weight	
Polymethylethoxysiloxane	68554-66-5	1 - 5 by weight	
Styrene acrylate based polymer	No Data	10 - 30 by weight	
Titanium Oxide	13463-67-7	10 - 30 by weight	
Tridymite silica	15468-32-3	5 - 10 by weight	
Undisclosed/Non-hazardous	No Data	1 - 5 by weight	
Water	7732-18-5	10 - 30 by weight	

SECTION 4 - FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Eye Contact:

Ensure adequate flushing of the eyes by separating the eyelids with

fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes,

while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or

give oxygen by trained personnel. Seek immediate medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control Ingestion:

center immediately. Never give anything by mouth to an unconscious

person.

Other First Aid: First Responders should provide for their own safety prior to rendering

assistance.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: Not determined. Auto Ignition Temperature: Not determined.

Lower Flammable/Explosive Not determined.

Limit:

Upper Flammable/Explosive

Limit:

Not determined.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Extinguishing Media: Use dry chemical or foam when fighting fires involving this material. Water

mist may be used to cool closed containers.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA),

MSHA/NIOSH (approved or equivalent) and full protective gear.

Unusual Fire Hazards: Material may spatter above 100 °C/212 °F

NFPA Ratings:

NFPA Health: 1
NFPA Flammability: 1

NFPA Reactivity: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Evacuate area and keep unnecessary and unprotected personnel from

entering the spill area.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods for containment: Contain spills with an inert absorbent material such as soil, sand or oil dry.

Methods for cleanup: Absorb spill with inert material (e.g., dry sand or earth), then place in a

chemical waste container. Provide ventilation. Clean up spills immediately

observing precautions in the protective equipment section.

SECTION 7 - HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use. Store away from direct heat or sunlight, sources of UV radiation, peroxides,

or free radicals.

Do not store in temperatures above 120 °F or below 48 °F. Keep away

from direct sunlight.

Work Practices: Handle in accordance with good industrial hygiene and safety practices.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

StoColor Lotusan

Product Code: 80217

Revision Date: 3/1/2017

3 of 8

Engineering Controls: Use appropriate engineering control such as process enclosures, local

exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the

personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29

CFR 1910.133, OSHA eye and face protection regulation, or the European

standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent

skin contact. Consult manufacturer's data for permeability data.

Hand Protection Description: Nitrile rubber or natural rubber gloves are recommended.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge

or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying

respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an

eyewash and a deluge shower safety station.

PPE Pictograms:



EXPOSURE GUIDELINES

Cristobalite silica:

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 Respirable fraction (R)

<u>Crystaline silica (Quartz)</u>:

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 Respirable fraction (R)

Slight

<u>Titanium Oxide</u>:

Odor:

Guideline ACGIH: TLV-TWA: 10 mg/m3

Notes: Only established PEL and TLV values for the ingredients are listed.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid.

Boiling Point: Not determined.

Melting Point: 0°C (32°F)

Specific Gravity: > 1

Solubility: Miscible in water

Vapor Density: Not determined.

Vapor Pressure: Not determined.

Percent Volatile: Data not available.

Evaporation Rate: Not determined.

pH: 7.5 - 10

Flash Point: Not determined.

StoColor Lotusan
Revision Date: 3/1/2017
Product Code: 80217
4 of 8

Auto Ignition Temperature: Not determined.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under recommended handling and storage conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: Heat, flames, ignition sources, and sparks. Incompatible materials.

Freezing or temperatures below 32 deg. F.

Incompatible Materials: Water reactive materials.

Special Decomposition

Products:

Thermal decomposition can lead to release irritant fumes and toxic gases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica:

RTECS Number: VV7328000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 197

mg/m3/6H/26W (Intermittent) [Lungs, Thorax, or Respiration - Changes

in lung weight] (RTECS)

Cristobalite silica:

RTECS Number: VV7325000

Inhalation: Inhalation - Mouse TCLo - Lowest published toxic concentration: 43

mg/m3/5H/9D (Intermittent) [Lungs, Thorax, or Respiration - Pleural

effusion Lungs, Thorax, or Respiration - Other changes]

Inhalation - Mouse TCLo - Lowest published toxic concentration: 70 mg/m3/5H/12D (Intermittent) [Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Fibrosis (interstitial)

Lungs, Thorax, or Respiration - Other changes] (RTECS)

Crystaline silica (Quartz):

RTECS Number: VV7330000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 248

mg/m3/6H [Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (intermediary) - Other proteins Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of inflammation] Inhalation - Rat TCLo - Lowest published toxic concentration: 248 mg/m3/6H [Lungs, Thorax, or Respiration - Changes in lung weight Immunological Including Allergic - Increase in cellular immune response Biochemical - Metabolism (intermediary) - Effect on inflammation or

mediation of inflammation]

Inhalation - Rat TCLo - Lowest published toxic concentration : 200 mg/kg [Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Other changes Nutritional and Gross Metabolic -

Changes in iron]

Inhalation - Mouse TCLo - Lowest published toxic concentration: 40 mg/kg

[Lungs, Thorax, or Respiration - Other changes]

Inhalation - Mouse TCLo - Lowest published toxic concentration : 40 mg/kg [Immunological Including Allergic - Decrease in cellular immune response] Inhalation - Rat TCLo - Lowest published toxic concentration : 1 mg/kg

(RTECS)

StoColor Lotusan
Revision Date: 3/1/2017
Product Code: 80217
5 of 8

Ingestion: Oral - Rat TDLo - Lowest published toxic dose : 120 gm/kg [Gastrointestinal

- Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS)

Titanium Oxide:

RTECS Number: XR2275000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration : 1 mg/kg [

Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of inflammation]

(RTECS)

Ingestion: Oral - Rat TDLo - Lowest published toxic dose: 60 gm/kg [Gastrointestinal

- Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No environmental information found for this product.

Environmental Fate: No environmental information found for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial

regulations.

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.

DOT Hazard Class: Non regulated.

IATA Shipping Name: Non regulated.

IMDG UN NUmber: Non regulated.

SECTION 15 - REGULATORY INFORMATION

SARA: This product does not contain any chemicals which are subject to the

reporting requirements of the Superfund Amendments and Reauthorization

Act of 1986 (SARA) Title III (40CFR, Part 372).

California PROP 65: The following statement(s) are provided under the California Safe Drinking

WARNING This product contains a chamical known to the State of

WARNING! This product contains a chemical known to the State of

California to cause cancer.

StoColor Lotusan

Revision Date: 3/1/2017

Product Code: 80217
6 of 8

Canada WHMIS: Xi - Irritant

EU Class: Irritant.

In accordance to Regulation (EC) No 1272/2008 on the classification,

labelling and packaging of substances and mixtures

Risk Phrases: R36/37/38 - Irritating to eyes, respiratory system and skin.

Safety Phrase: S23 - Do not breathe gas/fumes/vapour/spray.

S37 - Wear suitable gloves.

Amorphous silica:

Listed TSCA Inventory Status: Canada DSL: Listed

Cristobalite silica:

TSCA Inventory Status: Listed Listed Canada DSL:

Crystaline silica (Quartz):

TSCA Inventory Status: Listed Canada DSL: Listed

Octyl triethoxy silane:

Listed TSCA Inventory Status: Listed Canada DSL:

Polymethylethoxysiloxane:

TSCA Inventory Status: Listed Canada DSL: Listed

Titanium Oxide:

Listed TSCA Inventory Status: Canada DSL: Listed

SECTION 16 - ADDITIONAL INFORMATION

1* HMIS Health Hazard: HMIS Fire Hazard: 1 HMIS Reactivity: n

HMIS Personal Protection:

SDS Creation Date: July 08, 2013 SDS Revision Date: July 08, 2013

The information and recommendations contained herein are, to the best of Disclaimer:

Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or

reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered

for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its

particular use.

Χ

StoColor Lotusan Product Code: 80217 Revision Date: 3/1/2017

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.

StoColor Lotusan
Revision Date: 3/1/2017

Product Code: 80217
8 of 8