


PRODUCT BULLETIN

Sto Stencil

Product Number: 81725










PRODUCT DESCRIPTION

Sto Stencils are adhesive backed stencil sheets used with StoSignature Brick or StoSignature Stone to create the look and feel of real masonry in StoTherm ci, StoPowerwall, StoQuik Silver or Sto Ventec R systems.

FEATURES	BENEFITS
Made from recycled HIPS (High Impact Polystyrene)	Reduced waste, sustainable product
Thick stencils: .023" or .060"	Creates the realistic look of brick or stone

PRODUCT SELECTION DATA

Sto Part No.	Depiction	Sto Part Name	Brick Dimensions (inches) W x H x grout width	Coverage Ft ² /box
81725-007		Stencil Small New York Block 0.23 Box	11.5 x 3.5 x 0.375	450
81725-008		Stencil Small New York Block 0.60 Box	11.5 x 3.5 x 0.375	300
81725-009		Stencil 8x8 Tile Box	8 x 8 x 0.5	480
81725-010		Stencil Recycled Wall Brick 0.23 Box	7.75 x 2.5 x 0.375	480
81725-011		Stencil Recycled Wall Brick 0.60 Box	7.75 x 2.5 x 0.375	300
81725-014		Stencil Standard Brick 3/8" 0.23 Box	8 x 2.25 x 0.375	425
81725-015		Stencil Standard Brick 3/8" 0.60 Box	8 x 2.25 x 0.375	300
81725-012	N/A	Stencil Soldier Course Brick 3/8" 0.23 Box	8 x 2.25 x 0.375	300

Packaging
Sheets are packed flat in corrugated cardboard boxes










Shelf Life
12 months, if properly stored.

Storage
Protect from extreme heat [90°F (32°C)], freezing and direct sunlight.

PRODUCT BULLETIN

Sto Stencil

Product Number: 81725









81725-013	N/A	Stencil Soldier Course Brick 3/8" 0.60 Box	8 x 2.25 x 0.375	300
81725-016		Stencil Cinder Block Box	16.25 x 8 x 0.5	450
81725-019		Stencil Standard Brick 1/2 0.23 Box	8 x 2.25 x 0.5	450
81725-020		Stencil Standard Brick 1/2 0.60 Box	8 x 2.25 x 0.5	300
81725-017	N/A	Stencil Soldier Course Brick 1/2" 0.23 Box	8 x 2.25 x 0.5	300
81725-018	N/A	Stencil Soldier Course Brick 1/2" 0.60 Box	8 x 2.25 x 0.5	300
81725-021	N/A	Stencil Large Cinder Block Box	12 x 24 x 0.5	400
81725-022	N/A	Stencil Norman Brick 0.23 Box	11.625 x 2.25 x 0.375	400
81725-023	N/A	Stencil Norman Brick 0.60 Box	11.625 x 2.25 x 0.375	400
81725-001		Stencil Running bond Box	7.5 x 3.375 x 0.5	480
81725-024	N/A	Stencil Ashlar Slate 0.23 Box	Varies x 0.5	450
81725-025	N/A	Stencil Ashlar Slate 0.60 Box	Varies x 0.5	300
81725-026	N/A	Stencil Old Mill Brick 0.23 Box	7.4375 x 2.25 x 0.375	400
81725-027	N/A	Stencil Old Mill Brick 0.60 Box	7.4375 x 2.25 x 0.375	300
81725-002		Stencil Border Brick Box	8 x 3.5 x 0.5	300
81725-003		Stencil Basket weave Box	8 x 3.75 x 0.5	480
81725-004		Stencil Herringbone Box	8 x 4 x 0.5	480
81725-005		Stencil Stone Box	Varies	480
81725-006		Stencil Wall Brick Box	7.75 x 2.5 x 0.375	480

PRODUCT BULLETIN

Sto Stencil

Product Number: 81725

APPLICATION

A. Apply StoPrime® UV over the basecoat. The primer is designed to remain exposed to open weather and will ultimately appear as mortar joints in the finished design. Allow to dry.		E. Where stencils abut one another, use appropriate sized reinforced masking tape to secure and hold the individual stencils in position to achieve the desired effect.	
B. Prior to placing the stencils, snap guidelines to ensure proper alignment, paying close attention to rough openings, corners and other details to achieve a final consistent appearance.		F. When applying Sto Finish trowel in all four directions to ensure the stencil cells are properly filled.	
C. Once the wall surface is properly laid out, remove the adhesive tape from the stencils and apply them to the surface in their designated positions		G. Once the cells are completely filled, trowel horizontally along the mortar joints to ensure an even surface. Make sure to align the trowel on the mortar joint.	
D. Pass over the stencils with a paint roller and a PVC sleeve to help smooth out the stencil. Take caution if using a trowel as it may damage the stencil.		H. When the finish is completely dry, carefully remove the stencil to avoid damaging the finish.	

For more information on application techniques, refer to the StoSignature Brick or StoSignature Stone Application Guides/Videos or individual product bulletins.

Sto Canada Ltd.
1821 Albion Road
Unit 1 – 2
Etobicoke, ON M9W 5W8
CANADA
Tel: 416 855 0460
www.stocanada.com

Revision Number:
A4.0
Date: 06/2020

ATTENTION

This product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Canada Ltd. website, www.stocanada.com