


PRODUCT BULLETIN

Sto EPS Insulation Board



PRODUCT DESCRIPTION

Sto EPS Insulation Board is a rigid cellular expanded polystyrene insulation board intended for use in the StoTherm® ci exterior wall system.

FEATURES	BENEFITS
Lightweight, easy to cut, score, shape, and rasp	Worker friendly, easy to achieve aesthetics
Fully tested for fire exposure and durability	Built-in compatibility of wall system components, peace of mind, for use on all Types of construction
Continuous insulation	Simplifies design to achieve required RSI-value or U-factor in wall construction

REGULATORY COMPLIANCE

- Complies with CAN/ULC S701.1, *Standard for Thermal Insulation, Polystyrene, Boards and Pipe Covering, Type 1*
- Meets requirements of the National Building Code of Canada-2015 and 2020 as a component of StoTherm ci. Refer to CCMC Evaluation Report 12416-R, *StoTherm ci*, and Intertek Design Listings STO/WEIFS 15-01 and STO/WEIFS 25-01

PACKAGING and SIZES

Packaged in yellow polyethylene bags, 600 x1200mm (2 x 4 ft) boards at 50-165mm (2-6.5 inch) thickness in increments of 12.7mm (1/2 inch).

SHELF LIFE

18 months, if properly stored in original packaging.

STORAGE

The product is combustible. Protect or store away from sources of high heat, ignition, sparks, flames, flammable or volatile materials. Store in original packaging off the ground in a dry location. Protect from UV exposure and avoid covering with dark colored tarps or other coverings which can cause heat build-up and surface deformation.

INSULATING VALUE

RSI 0.65 K·m² /W (R-3.7 F·ft² ·h/Btu) at 25 mm (1") thick.

INSTALLATION

Refer to *Sto Canada Installation Guide for StoTherm ci* at www.stocanada.com

LIMITATIONS

- Service temperature limit: -53.9 to +73.9°C (-65 to +165°F)
- A protective barrier or thermal barrier is required as specified in the appropriate building code to separate this product from interior space
- For other limitations of use with respect to building codes refer to CCMC 12416-R and Intertek Design Listings

LIMITED WARRANTY

This product is subject to a written limited warranty which can be obtained free of charge from Sto Canada Ltd.

HEALTH & SAFETY

Refer to SDS at www.stocanada.com

Sto Canada Ltd. 1821 Albion Road, Unit 1-2 Etobicoke, ON M9W 5W8 Tel: (416) 855-0460 Toll Free: 1-800-786-5234 www.stocanada.com	Revision No. 000 Date: 09/2026	ATTENTION This product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Canada Ltd website, www.stocanada.com
---	---	---