

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: Stolit X Medium

Product Code: 81525 SDS Manufacturer Number: 81525


Product Use/Restriction: Waterbased Acrylic Coating.

Manufacturer Name: Sto Corp.

6175 Riverside Drive, SW

Atlanta, Georgia 30331 General Phone Number: (404) 346-3666 Emergency Phone Number: (800) 424-9300 February 23, 2017 SDS Creation Date: February 23, 2017 SDS Revision Date:

(M)SDS Format:





* Chronic Health Effects

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Pictograms:



Signal Word:

Eye Irritant, Category 2. Skin Irritant, Category 2. GHS Class:

Hazard Statements: Causes eye irritation.

Precautionary Statements:

Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Emergency Overview: WARNING! Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: May cause irritation. Skin: May cause irritation.

Inhalation: $\label{prolonged} \mbox{Prolonged or excessive inhalation may cause respiratory tract irritation.}$

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Calcium carbonate	1317-65-3	40 - 60 by weight	215-279-6
Water	7732-18-5	10 - 30 by weight	231-791-2
Acrylic polymer	No Data	5 - 15 by weight	
Crystaline silica (Quartz)	14808-60-7	1 - 5 by weight	238-878-4
Crystalline Silica (Cristobalite)	14464-46-1	1 - 5 by weight	238-455-4
Muscovite Mica	12001-26-2	1 - 5 by weight	272-489-0

Stolit X Medium Product Code: 81525 Revision:: 02/23/2017

Titanium Oxide 13463-67-7 0.1 - 1.0 by weight 236-675-5

SECTION 4: FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.Eve Contact:

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Ingestion:

Other First Aid: First Responders should provide for their own safety prior to rendering assistance.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: Not determined. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not determined. Upper Flammable/Explosive Limit: Not determined.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to

minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Extinguishing Media: Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool

closed containers.

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) Protective Equipment:

and full protective gear

Unusual Fire Hazards: Material may spatter above 100 °C/212 °F.

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity 0

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods for containment: Contain spills with an inert absorbent material such as soil, sand or oil dry.

Methods for cleanup: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment

section.

SECTION 7: HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Storage:

Store away from direct heat or sunlight, sources of UV radiation, peroxides, or free radicals. Do not store in temperatures above 49°C (120 °F) or below 9°C (48 °F). Keep away from direct

sunlight.

Work Practices: Handle in accordance with good industrial hygiene and safety practices.

Hygiene Practices: Wash thoroughly after handling.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general **Engineering Controls:**

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Product Code: 81525

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye Eye/Face Protection:

and face protection regulation, or the European standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult

manufacturer's data for permeability dat

Hand Protection Description: Nitrile rubber or natural rubber gloves are recommended. Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower

safety station

PPE Pictograms:



EXPOSURE GUIDELINES

Crystaline silica (Quartz):

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 (R)

Crystalline Silica (Cristobalite):

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 Respirable fraction (R)

Muscovite Mica:

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 Respirable fraction (R)

<u>Titanium Oxide</u>:

TLV-TWA: 10 mg/m3 Guideline ACGIH:

Only established PEL and TLV values for the ingredients are listed. Notes:

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Liquid. Physical State Appearance:

Odor: Sliaht.

Boiling Point: Not determined. Melting Point: 0°C (32°F)

Specific Gravity:

Solubility: Miscible in water. Vapor Density: Not determined. Vapor Pressure: Not determined. Percent Volatile: Data not available. Evaporation Rate: Not determined.

pH: 7.5 - 10

Flash Point: Not determined. Auto Ignition Temperature: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under recommended handling and storage conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Heat, flames, ignition sources, and sparks. Incompatible materials. Freezing or temperatures below 0°C (32°F). Conditions to Avoid:

Incompatible Materials: Water reactive materials.

Special Decomposition Products: Thermal decomposition can lead to release irritant fumes and toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Calcium carbonate :

RTECS Number: EV9580000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration : 250 mg/m3/2H/24W (Intermittent) [

Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis)]
Inhalation - Rat TCLo - Lowest published toxic concentration : 84 mg/m3/4H/40W (Intermittent) [
Lungs, Thorax, or Respiration - Fibrosis (interstitial) Liver - Other changes Kidney/Ureter/Bladder - Other changes] (RTECS)

Crystaline silica (Quartz):

RTECS Number: VV7330000

Inhalation:

Inhalation - Rat TCLo - Lowest published toxic concentration : 248 mg/m3/6H [Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (intermediary) - Other proteins Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of inflammation] Inhalation - Rat TCLo - Lowest published toxic concentration : 248 mg/m3/6H [Lungs, Thorax, or Respiration - Changes in lung weight Immunological Including Allergic - Increase in cellular immune response Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of inflammation 1

inflammation 1

Inhalation - Rat TCLo - Lowest published toxic concentration : 200 mg/kg [Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Other changes Nutritional and Gross Metabolic - Changes in iron]

Inhalation - Mouse TCLo - Lowest published toxic concentration : 40 mg/kg [Lungs, Thorax, or

Respiration - Other changes]

Stolit X Medium Product Code: 81525 Revision:: 02/23/2017

Inhalation - Mouse TCLo - Lowest published toxic concentration : 40 mg/kg [Immunological Including

- Decrease in cellular immune response]

Inhalation - Rat TCLo - Lowest published toxic concentration : 1 mg/kg (RTECS)

Oral - Rat TDLo - Lowest published toxic dose : 120 gm/kg [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS)

Crystalline Silica (Cristobalite):

RTECS Number: VV7325000

Inhalation:

Inhalation - Mouse TCLo - Lowest published toxic concentration : 43 mg/m3/5H/9D (Intermittent) [Lungs, Thorax, or Respiration - Pleural effusion Lungs, Thorax, or Respiration - Other changes] Inhalation - Mouse TCLo - Lowest published toxic concentration : 70 mg/m3/5H/12D (Intermittent) [Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Fibrosis (interstitial) Lungs, Thorax, or Respiration - Other changes] (RTECS)

Titanium Oxide:

Ingestion:

RTECS Number: XR2275000

 $Inhalation - Rat\ TCLo - Lowest\ published\ toxic\ concentration: 1\ mg/kg\ [\ Lungs,\ Thorax,\ or\ Respiration\ -\ Other\ changes\ Biochemical\ -\ Metabolism\ (intermediary)\ -\ Effect\ on\ inflammation\ or\ mediation\ of\ inflammation\]\ (RTECS)$ Inhalation:

Oral - Rat TDLo - Lowest published toxic dose : 60 gm/kg [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS) Ingestion:

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No environmental information found for this product. Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated. DOT Hazard Class: Non regulated.

IATA Shipping Name: Non regulated.

IMDG UN Number: Non regulated.

SECTION 15: REGULATORY INFORMATION

SARA: This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to cause cancer.

Canada WHMIS: Xi - Irritant.

EU Class: Irritant.

In accordance to Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Risk Phrases: R36/37/38 - Irritating to eyes, respiratory system and skin.

S23 - Do not breathe gas/fumes/vapour/spray. S37 - Wear suitable gloves. Safety Phrase:

Calcium carbonate:

TSCA Inventory Status: Listed 215-279-6 EC Number:

Water:

California PROP 65:

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 231-791-2

Crystaline silica (Quartz):

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 238-878-4

Crystalline Silica (Cristobalite):

TSCA Inventory Status: Listed Canada DSL: Listed

> Stolit X Medium Product Code: 81525 Revision:: 02/23/2017

> > Page 4 of 5

EC Number: 238-455-4

Muscovite Mica:

TSCA Inventory Status: Listed
Canada DSL: Listed

EC Number: 272-489-0

<u>Titanium Oxide</u>:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 236-675-5

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1*
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

SDS Creation Date: February 23, 2017
SDS Revision Date: February 23, 2017

SDS Format:

Disclaimer:

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

Stolit X Medium Product Code: 81525