


StoGuard® Waterproof Air Barrier Frame Construction

Rough Opening Protection with StoGuard Fabric and StoGuard Tape at Sill (for abuse-resistance at sill)

Detail No.: 20.20FT

Date: March 2014



Notes:

- 2) StoGuard waterproof air barrier membrane options:
 - A) Sto EmeraldCoat®
 - B) StoGuard VaporSeal™
 - C) Sto Gold Coat®
 (Use with StoTherm NExT EIF systems)
- 2) Prepare opening prior to the installation of the window or mechanical equipment. Provide sill wedge or other means for positive slope to exterior at sill.
- 3) Incorporate flashing as illustrated in 20.23a or as per other details where flashing is shown.
- 4) The complete installation of window or mechanical equipment must include an air seal between the object and the StoGuard protection, inboard of the outer perimeter weather seal.
- 5) Refer to Sto specifications and product bulletins for detailed information on substrates and Sto material options. Additional water-resistant barrier/slip sheet required behind some claddings not shown. Refer to Sto Detail 20.00b for additional information.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com