

StoGuard® Waterproof Air Barrier **Frame Construction**

Balcony Floor to Wall Transition with Deck Coating

Sheathing coated with StoGuard waterproof air barrier membrane (Note 1) Quarter-round backer rod Compatible Sealant Balcony slab Compatible waterproof deck coating. Extend minimum 4 inches (102 mm) onto vertical surface Property of Sto Corp. All Rights Reserved

Date: March 2014

Detail No.: 20.30a

Notes:

- 1]StoGuard waterproof air barrier membrane options:
 - A) Sto EmeraldCoat®
- B) StoGuard VaporSeal™
- C) Sto AirSeal™
- D) Sto Gold Coat® (Use with StoTherm NExT
- EIF systems) 2] Provide positive slope to
- direct water away from wall. Verify compatibility of waterproof deck membrane materials with StoGuard waterproof air barrier membrane.
- 3] Refer to Sto specifications and product bulletins for detailed information on substrates and Sto material options. Additional waterresistive barrier/slip sheet required behind some claddings not shown. Refer to Sto Detail 20.00b for additional information.

IMPORTANT: Components not identified as Sto are furnished by other manufactur-ers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Attention

www.stocorp.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. STO CORP DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.