

StoQuik® Silver DrainScreen™ Outside Corner with Sto Mesh Corner Bead Wood Frame

Wood Frame Sheathing StoGuard Joint Treatment (See Sto Detail 11.09 DS) StoGuard[®] Air and Moisture Sto DrainScreen $^{\mathsf{TM}}$ Cement Board Sto Base Coat and Sto-Mesh Corner Bead Sto Base Coat and Sto Mesh Sto Primer (optional) Sto Finish (smooth or textured) Property of Sto Corp. All Rights Reserved.

Notes:

 Refer to Sto Detail series 20.xx for additional information regarding StoGuard[®] products and installation.

Detail No.: 11.54 DS

Date: August 2015

- Refer to Sto Specification QS 200 DS for complete information on design requirements and installation of StoQuik[®] Silver products and systems.
- Embed Sto Mesh Corner Bead in Sto base coat along outside corner and allow base coat to dry.
- Apply Sto base coat and Sto Mesh to the entire prepared surface of the cement board, fully overlapping the Sto Mesh Corner Bead.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

www.stocorp.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.