



Sto TurboStick™

Fast, Convenient, Cost Effective
Foam Adhesive

Choose the industry's most versatile liquid polyurethane foam adhesive for EIFS and other claddings.

Sto TurboStick™

Innovative technology delivers speed and value.



Sto TurboStick™ has many advantages when used to install insulation boards in EIFS and other insulated claddings:

- Liquid polyurethane foam adhesive effectively adheres to most insulation boards, including EPS (Expanded PolyStyrene), XPS (Extruded PolyStyrene) and Polyisocyanurate
- Adhesive foam adheres to most substrates, such as:
 - Glass mat-faced gypsum boards
 - StoGuard fluid applied membrane
 - OSB
 - Plywood
 - Huber Zip Sheathing
 - CMU (Concrete Masonry Units)
 - Galvanized Metal
- Foam expands and cures based on moisture in the air
- In most conditions, you can rasp in about two hours (for StoTherm EIFS)
- Versatile product can be used for other tasks, including filling voids between insulation boards
- Use as adhesive for insulation in StoEnergy Guard
- Contains no VOCs
- Can be used down to 33°F (1°C)

Why Sto TurboStick is Better

Features	Benefits
Foam Adhesive	Good adhesion for most insulation boards Faster application Expands and cures quickly Faster to rasp insulation boards No VOCs
Lightweight cylinder	No mixing required Simple, easy to use Increases production time by 20% Saves space on scaffolds 1 cylinder = 5-6 bags of powder adhesive
Screw-on hose and pistol	Versatile – use for other tasks
Adhesive Attachment	Eliminates searching for structural members Eliminates perforations in air barrier Eliminates thermal bridging at fasteners

Compared to powdered or two-component adhesives, Sto TurboStick™ delivers unmatched convenience and efficiency:

- No mixing or clean-up is required; simply shake the canister by hand
- Preparation is quick – just screw on hose and pistol
- Production speed increases by about 20%
- Simple and compact cylinder saves space on scaffolds
- Each cylinder adheres 625-675 sq. ft. – equal to 5-6 bags of powder adhesive
- Rasp foam the same day – cut a day from the production cycle

Sto Corp.

3800 Camp Creek Parkway
Building 1400, Suite 120
Atlanta, GA 30331
Phone 404-346-3666
Toll Free 1-800-221-2397
Fax 404-346-3119
www.stocorp.com

Questions or comments?

Visit www.stocorp.com, call (800) 221-2397
or email marketingsupport@stocorp.com.



ATTENTION

The product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS, WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.