

StoTherm[®] ci ProD Termination at Grade -Sheathing Overlapping Slab or Foundation

Sto Base Coat (with Sto Mesh Embedded) Sto Mesh Sto EPS ProD or Sto GPS ProD Sto Primer (Optional) Insulation Board Sto Finish Light Gauge Steel Stud Framing StoGuard® Air and Moisture Barrier Sheathing-Sto Adhesive Sto EPS ProD or Sto GPS ProD Starter Board, Pre-Wrapped StoGuard® Air and Moisture Barrier Detail Component Flashing, Sloped Terminate Assembly 6" (152 mm) Above Grade, min. Backer Rod & Sealant w/ Weep Holes StoGuard® Transition Membrane Embedded in StoGuard® Air and Moisture Barrier (Protect with StoCoat Acryl Plus or Flashing) Property of Sto Corp. All Rights Reserved

Notes:

1. Terminate system minimum 6" (15.2 cm) above finished grade, higher for areas with heavy snow accumulations, or where required by code.

Detail No.: 54s.03B

Date: April 2016

- 2. Ultra-high impact resistance recommended at all ground floors to a minimum height of 6'-0" (1.8 m) above finished grade and other areas accessible to pedestrian traffic, abnormal stress or impact.
- Refer to StoTherm ci ProD System Bulletins and Specifications, Sto Product Bulletins, Tech Hotlines, and Sto Installation and Maintenance Guides for complete information.
- Refer to applicable CCMC Evaluation Reports for building code compliance information.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install Sto products. Refer to project specific contract documents.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

www.stocorp.com

