

StoTherm[®] ci XPS ProD Sign Attachment

Sto TurboStick[™] Adhesive-StoGuard® Air and Light Gauge Steel -Moisture Barrier Stud Framing Dow STYROFOAMTM Sheathing-Panel Core 20 ProD Insulation Board Sto Base Coat (with Sto Mesh Embedded) Sto Mesh Sto Primer (Optional) Sto Finish Washer Behind Sign Set in Sealant Wood Blocking Hole Drilled in EIFS and Lined with Sealant Neutral Cure Sealant Bolt w/ Washers PVC or Stainless Steel Sleeve at Each End (Sleeve Extends From Finish Through Blocking, Shown Partial Length for Clarity) Dow Property of Sto Corp. All Rights Reserved

Notes:

1. Blocking not required where solid substrate or wood-based sheathing is capable of supporting the sign (or other attached object). Use appropriate fasteners for attachment.

Detail No.: 55s.71

Date: April 2016

- Refer to StoTherm ci XPS ProD System Bulletins and Specifications, Sto Product Bulletins, Tech Hotlines, and Sto Installation and Maintenance Guides for complete information.
- Refer to applicable Intertek listing for building code compliance information.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install Sto products. Refer to project specific contract documents.

ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

www.stocorp.com