


## StoTherm® ci Mineral Soffit: Uninsulated and Vented



## Notes:

1. Prevent "communication" of vented air space with conditioned interior air to reduce the likelihood of condensation on materials in the vented space.

Detail No.: 56s.31 CAE

Date: February 2019

- 2. Typical soffit board is gypsum sheathing in compliance with ASTM C 1177. Refer to Sto Specification No. F601S and Sto Detail Series 14.xx.
- 3. Refer to StoTherm ci System Bulletins and Specifications, Sto Product Bulletins, Tech Hotlines, and Sto Installation and Maintenance Guides for complete information.
- 4. Mechanical Fasteners not shown. See Sto Detail 56s.02 for mechanical attachment pattern and additional information.
- 5. Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

## **ATTENTION**

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

www.stocanada.com

