


# StoTherm XPS for Insulated Concrete Forms (ICF)



Detail No.: EPD 17i.01 CAE  
Date: July 2020



Property of Sto Corp. All Rights Reserved.

## Notes:

A. Detail illustrates a generic Insulated Concrete Forms (ICF) that is suitable for Sto Coatings directly applied to the form without additional insulation

B. Forms suitable for direct application coatings have imbedded, non-metallic form ties positioned a minimum 1/2" (13 mm) from the outer surface.

C. Rasping the foam surface to provide a level surface for coatings shall not expose the form ties.

D. Concrete shall be allowed to cure for a minimum of 28 days prior to application of Sto coating materials.

E. There are no substitutions for the Sto products listed below.

## Sto Products:

1. Sto TurboStick Adhesive
2. Owens Corning C-IC Board
3. Sto Mesh
4. Sto Flexyl Base Coat
5. StoPrime Sand Primer
6. Sto Finish Components:
  - a. Stolit® & Stolit®Dark Colors: 1.0, 1.5, R1.5 and Freeform
  - b. Stolit®Lotusan & Stolit®Lotusan Dark Colors: 1.0, 1.5, R1.5 and Freeform

## ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.

STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, [www.stocorp.com](http://www.stocorp.com).

[www.stocanada.com](http://www.stocanada.com)

