


StoPowerwall® One-Piece Control Joint

Detail No.: 4.52

Date: December 2015



Notes:

- 1] Provide one-piece control joints at minimum 144 ft² (13.4 m²) intervals and below window, door, and similar openings in the wall construction.
- 2] Do not exceed length to width ratio of 2.5:1 in joint layout and do not exceed 18 ft (5.5 m) in any direction without a joint.
- 3] Lap metal reinforcement (lath) over joint accessory flanges and wire tie. Alternatively, install metal reinforcement, snip (cut) at line of accessory, and wire tie joint accessory over metal reinforcement. Metal reinforcement MUST BE DISCONTINUOUS BENEATH THE ACCESSORY.
- 4] Comply with ASTM 1063.
- 5] See detail 4.01 for StoGuard product options

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

www.stocorp.com

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.