


StoPowerwall® Joint at Inside Corner: Different Substrates

Detail No.: 4.53

Date: December 2015



Notes:

- 1] Install Sto joint treatment approximately 4" (100mm) onto each face. Refer to Sto Detail 4.09. (StoGuard® Mesh is not recommended over masonry substrate.) Do not extend StoGuard on CMU beyond the expanded flange of the accessory.
- 2] Apply StoGuard over sheathing substrate.
- 3] Inside corner joints are not recommended where the substrate construction on either side of the corner is the same.
- 4] StoPowerwall Stucco applied directly to CMU functions as a water and air resistant assembly.
- 5] Please see detail 4.01 for StoGuard product options.

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

Attention

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.

www.stocorp.com