

## StoPowerwall® DrainScreen™ Outside Corner

**Wood Frame Sheathing** Sto joint treatment StoGuard® Waterproof Air Barrier Membrane **Code Compliant Water Resistive Barrier** Sto DrainScreen™ **Galvanized Expanded** Diamond Mesh Metal Lath **Corner Bead Filled Solid** with StoPowerwall® StoPowerwall® **Sto Primer** Sto Finish (smooth or textured) Property of Sto Corp. All Rights Reserved.

## **Notes:**

 Install Sto Joint Treatment around sheathing joint at the outside corner. (See Sto Detail 5.09 DS)

Detail No.: 5.54 DS

**Date: October 2014** 

- Install galvanized expanded diamond mesh metal lath continuous around corner without break for minimum 24" (610mm).
- 3. Attach corner bead over lath.
- Metal accessories are susceptible to corrosion in costal environments. Metal corner beads with solid metal noses are susceptible to corrosion in exposed exterior applications.

## **Options:**

StoGuard® Waterproof Air Barrier Membrane options:

- a. Sto EmeraldCoat® (high perm)
- b. StoGuard<sup>®</sup> VaporSeal<sup>™</sup> (vapor impermeable).

IMPORTANT: Components not identified as Sto are furnished by other manufacturers and are not necessarily installed by trades who install the Sto products. Refer to project specific contract documents.

ATTENTION www.stocorp.com

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, of for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components.